

Proofing Paper Commercial Semimatte

For Use With:

EPSON Stylus® Photo 2200	EPSON Stylus Pro 9000
EPSON Stylus® Pro 7000	EPSON Stylus Pro 9500
EPSON Stylus Pro 7500	EPSON Stylus Pro 9600 ¹
EPSON Stylus Pro 7600 ¹	EPSON Stylus Pro 10000 ²



Product Information

Designed with a commercial grade base color, the semimatte surface finish on this proofing media is ideally suited for simulating the commercial printing applications most commonly used in high-end sheetfed printed products such as brochures, collateral, book covers and posters. Coated with exacting standards, this paper displays outstanding short term stability when used in conjunction with Epson professional inks. Its medium weight combined with a wide color gamut makes this the perfect choice for commercial proofing applications.

Like all of Epson's innovative media, this paper is engineered to give you the highest resolution and color saturation possible. As always, EPSON supplies guarantee EPSON quality.

¹ Photographic dye version and UltraChrome ink version

² Photographic dye version and archival ink version

Features/Benefits

- Highest color gamut available for accurate color reproduction
- Base color and gloss level designed to match commercial press applications
- Excellent short term stability for exacting proofing standards
- Dries instantly for easy handling with Epson inks

Feature Checklist

Feature	Performance	Additional Comments
Indoor/outdoor usage	Indoor use only	
Lightfastness	Over 100 years EPSON Archival Ink Over 40 years UltraChrome Ink 5 years Photographic Dye Ink	Lightfastness ratings are based on accelerated testing of prints on specialty media, displayed indoors, under glass. Lightfastness only estimates the life of the ink, not the media.
Gas-fastness	Excellent with EPSON Archival and UltraChrome Ink; poor with dye-based ink	With regard to dye-based images, lamination or framing under glass greatly increases gas-fastness and the life of the print.
Resistance to water	Good	Bleeding does not occur with incidental water contact. However, encapsulated lamination is recommended in wet conditions.
Ink drying time	Immediate (less than 30 seconds)	Ink is dry to the touch after printing. However, it takes 24 hours before it cures and becomes durable.
Handling requirements	Use care	Handle with care to avoid scratching and kinking.
Lamination feasibility	Hot or cold lamination	Lamination extends the life of the print and increases durability

Proofing Paper Commercial Semimatte

Technical Specifications

Basis weight	155 g/m ²
Thickness	6.5 mil
ISO brightness	88%
Opacity	91%
Hot lamination	Yes
Base material	RC Paper
Base color	Commercial
Surface finish	Semimatte
Core size	2"
Spindle	2" standard

Driver Setting

<i>Printer</i>	<i>Setting</i>
RIP	Proofing Paper Commercial Semimatte

Operating Specifications

Required temperature for optimum performance	60° – 80° F 15° – 25° C
Required humidity for optimum performance	40% – 60% RH

(Note: High humidity will prolong the drying time for lamination purposes.)

Ordering Specifications (Individual Boxes)

<i>Product Code</i>	<i>Product</i>	<i>UPC Code</i>
SO41668	13" x 50' roll	0-10343-84316-5
SO41658	24" x 100' roll	0-10343-84288-5
SO41659	36" x 100' roll	0-10343-84289-2
SO41660	42" x 100' roll	0-10343-84290-8

Packaging Specifications (Individual Boxes)

<i>Product Code</i>	<i>Dimensions (L x W x H)</i>	<i>Weight</i>
SO41668	13.6" x 3.6" x 3.6"	2.0 lb
SO41658	25.2" x 4.6" x 4.6"	7.1 lb
SO41659	37.5" x 4.6" x 4.6"	10.4 lb
SO41660	41.3" x 4.6" x 4.6"	15.2 lb

MSRP

<i>Product Code</i>	<i>Product</i>	<i>Cost</i>
SO41668	13" x 50' roll	\$49.00
SO41658	24" x 100' roll	132.00
SO41659	36" x 100' roll	182.00
SO41660	42" x 100' roll	224.00



Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.
3771 Victoria Park Avenue Toronto, Ontario M1W 3Z5

Epson Latin America
6303 Blue Lagoon Drive, Miami, FL 33126

Specifications are subject to change without notice. EPSON and EPSON Stylus are registered trademarks of Seiko Epson Corporation. UltraChrome, EPSON Archival and EPSON Photographic Dye are trademarks of Epson America, Inc. All other products and brand names are registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2002 Epson America, Inc. CPD-13832 5K 6/02 CL

Printed on Recycled Paper